

# PROSPECTOR PETRO 300



## Product Specification

### Application

For use in tank truck and in-plant operations to transfer gasoline, oil, ethanol blends and other petroleum base products up to 50% aromatic content. Designed for pressure, gravity flow, or full-suction service.

### Construction Tube

- Nitrile Synthetic Rubber, ARPM Class A (High Oil Resistance)

### Cover

- SBR Rubber; Wrapped Impression

### Reinforcement

- Spiral-plied Fabrics with Double Wire Helix

### Temperature Range

- 25 F / -32 C ~ 180 F / 82 C

### Design Factor

- 4:1

### Packaging

100' length, coiled, polywrapped

### Branding

CONTINENTAL PROSPECTOR (OIL+GAS LOGO) PETRO 300 MADE IN CANADA (3/4" Spiral Transfer Tape, Red Backing with Black Lettering)

### Coupling

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

## PROSPECTOR PETRO 300 #MAINIMAGE#

Order Codes: 543-306

ID (in)	ID (mm)	OD (in)	OD (mm)	Bend Radius (in.)	Bend Radius (mm)	Vacuum HG (in.)	Vacuum HG (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.53	64.30	6.0	152	29	737	300	2.07	1.28	1.910	
2-1/2	63.50	3.08	78.10	7.5	191	29	737	300	2.07	1.72	2.560	
3	76.20	3.58	90.90	9.0	229	29	737	300	2.07	2.08	3.090	
4	101.60	4.72	119.90	16.0	406	29	737	300	2.07	3.41	5.080	
6	152.40	6.86	174.20	24.0	610	29	737	300	2.07	6.33	9.410	