

Dry bulk material

EHK022



Construction

- **Tube:** Abrasion resistant, static dissipating synthetic rubber
- **Reinforcement:** High tensile synthetic textile with helical wire and antistatic copper wire
- **Cover:** Abrasion, ozone and weather resistant pin-pricked special synthetic rubber

Operating temperature

- -40°C to +70°C
- (-40°F to +158°F)

Application







- For suction and discharge of dry bulk materials, sand, gravel dry cement

Markets

- Construction
- Cement
- Oil & Gas exploration

Type of couplings

- Cam and groove
- Combination nipple

#													
	Part number	Hose I.D.		Hose O.D.		Max operating pressure		Burst pressure		Minimum bend radius		Weight	
	DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
EHK022-32BK	51	50.8	2.0	68.0	2.68	20	290	60	870	190	7.5	2.38	1.60
EHK022-40BK	63	63.5	2.5	82.0	3.23	20	290	60	870	240	9.4	3.17	2.13
EHK022-48BK	75	76.2	3.0	94.0	3.70	20	290	60	870	300	11.8	3.64	2.45
EHK022-64BK	102	101.6	4.0	122.0	4.80	20	290	60	870	420	16.5	5.19	3.49
EHK022-80BK	127	127.0	5.0	151.0	5.94	20	290	60	870	520	20.5	7.66	5.15
EHK022-96BK	152	152.4	6.0	178.0	7.01	20	290	60	870	655	25.8	9.90	6.65
EHK022-128BK	200	203.0	8.0	232.0	9.13	20	290	60	870	1025	40.4	15.43	10.37



Powering Business Worldwide

Eaton
 EMEA Headquarters
 Route de la Longeraie 7
 1110 Morges, Switzerland
 Eaton.eu

© 2021 Eaton
 All Rights Reserved
 June 2021

Eaton is a registered trademark.

All other trademarks are property of their respective owners.