


		Socket	Threaded connections	Flanged connections	Flow rate	Materials	Seals
	1" (DN25)	56 mm	¾", 1", 1¼" BSP and NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 250 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM
	2" (DN50)	70 mm	1½", 2" BSP and NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 900 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM
	2½" (DN65)	105 mm	2½", 3" BSP and NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 2.100 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM
	3" (DN80)	119 mm	3" BSP and NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 2.800 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM
	4" (DN100)	164 mm	4" BSP and NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 7.000 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM
	6" (DN150)	238 mm	6" BSP and NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 14.000 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM
	8" (DN200)	272 mm	8" NPT	ANSI, EN, TW, TTMA, JIS. Others on request.	Up to 23.000 L/min	Specified in configurator	FKM, NBR, EPDM, FFKM